

Emergency I-800-424-9300 Contact (intl.) I-352-323-3500

Endure™ Alcoholic Clarifier

1. Identification

Product Name: Endure™ Alcoholic Clarifier

Synonyms: N/A

Recommended Use: N/A Manufacturer: Cancer Diagnostics, Inc. 116 Page Point Circle Durham, NC 27703 1-877-846-5393 Item #: ED6, ED64

Restrictions on Use: N/A In Case of Emergency: Chemtrec US 1-800-424-9300 Infotrac International 1-352-323-3500

2. Hazards Identification

OSHA Hazard Classification(s):

Skin Corrosion - Category 1C Eye Damage - Category 1

Specific Target Organ Toxicity (single exposure) - Category 1 Specific Target Organ Toxicity (repeated exposure) - Category 2

Flammable Liquids - Category 2

Signal Word: Danger

Hazard Statement(s): Causes severe skin burns and eye damage. Causes serious eye damage. Causes damage to organs (respiratory system). May cause damage to organs (respiratory system, central nervous system, liver, blood) through prolonged or repeated exposure. Highly flammable liquid and vapor.

Pictogram(s):







Precautionary Statement(s): Prevention: Do not breathe dusts or mists. Wash body thoroughly after handling. Wear protective gloves, protective clothing, eye protection and face protection. Wear eye protection, face protection. Do not breathe dust, vapors. Do not eat, drink or smoke when using this product. Keep away from heat sources and open flame. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Response: If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Take off all contaminated clothing and wash it before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a doctor. Specific treatment (see first aid section on this label). If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue Rinsing If exposed or concerned: Call a doctor. Call a doctor if you feel unwell. In case of fire: Use water, dry chemical, CO2 or foam to extinguish.

Storage: Store locked up. Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local regulations.

Descriptions of Hazards not otherwise classified: N/A Percent of mixture with unknown acute toxicity: N/A

3. Composition and Information on Ingredients

Chemical Name	Common Name	CAS#	Concentration %
Denatured Ethyl Alcohol		64-17-5	Trade Secret
Glacial Acetic Acid		64-19-7	Trade Secret
Water		7732-18-5	Trade Secret

4. First Aid Measures



Emergency 1-800-424-9300 Contact (intl.) 1-352-323-3500

Endure™ Alcoholic Clarifier

Eye Contact: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact: If on skin (or hair): Take off immediately all contaminated clothing and wash before reuse. Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.

Inhalation: Remove to fresh air; give artificial respiration if breathing has stopped. Get medical advice/attention if you feel unwell.

Ingestion: Do not induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into the lungs. Get medical attention.

Symptoms: Irritation eyes, nose, throat; headache, dizziness, drowsiness, lassitude (weakness, exhaustion), narcosis; cough; liver damage; anemia; reproductive, teratogenic effects.

Recommendations for immediate medical care/special treatment: Get medical advice/attention if you feel unwell.

5. Fire- Fighting Measures

Extinguishing Media: Dry chemical, carbon dioxide, alcohol foam, water. Use water spray to cool fire-exposed containers and disperse vapors.

Fire Hazards (Chemical): OSHA classified Flammable Liquid

Special Protective Equipment: Fire fighters should use self-contained breathing apparatus and protective clothing.

Precautions for Firefighters: Carbon monoxide and unidentified organic compounds may be formed during combustion. Vapors can travel distances to ignition source and flash back. Cool fire exposed containers with water. Fine mist or spray may be flammable at temperatures below the flash point. When heated above the flash point this material emits flammable vapors which, when mixed with air, can burn or be explosive.

6. Accidental Release Measures

Emergency Procedures: Evacuate the area of all unnecessary personnel. Wear suitable protective equipment. Eliminate all sources of ignition and provide ventilation.

Protective Equipment: See section 8

Environmental Precautions: Prevent release to the environment by using barriers.

Containment and Clean-Up Procedures: Use barriers to prevent spreading. Collect spill in container. Call waste authorities.

7. Handling and Storage

Handling: Do not breathe vapors. Do not eat, drink or smoke when using this product. Keep away from heat, sparks, open flames, hot surfaces. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Storage: Store locked up. Store in a well-ventilated place. Keep cool. Keep container tightly sealed when not in use. Store away from sources of ignition, heat and open flame.

8. Exposure Controls/Personal Protection

OSHA Permissible Exposure Limits (PELs):

(· ===).				
Reagent	CAS#	OSHA PEL TWA		
Ethyl Alcohol	64-17-5	1000ppm		
Isopropyl Alcohol	67-63-0	400ppm		
Methyl Alcohol	67-56-1	200ppm		
Glacial Acetic Acid	64-19-7	10ppm		

ACGIH Threshold Limit Values (TLVs):

Reagent	CAS#	ACGIH PEL TLV	ACGIH STEL
Ethyl Alcohol	64-17-5	1000ppm	
Isopropyl Alcohol	67-63-0	200ppm	400ppm
Methyl Alcohol	67-63-0	200ppm	250ppm
Glacial Acetic Acid	64-19-7	10ppm	15ppm





Emergency I-800-424-9300 Contact (intl.) I-352-323-3500

Endure™ Alcoholic Clarifier

Engineering Controls: Use in a well ventilated area to prevent exposure. Maintain eyewash fountain and quick-drench facilities in work areas

Personal Protective Measures: Wear gloves, lab coat, eye protection and impervious footwear. Contact lenses should not be worn when working with this material.

Special PPE Requirements: If ventilation hood not available wear respirator.

9. Physical and Chemical Properties Section

Appearance: Colorless, Liquid Molecular Weight: N/A Molecular Formula: N/A

pH: N/A

Boiling Point and Boiling Range: N/A **Melting Point/Freezing Point:** N/A

Flash Point: Approx 65°F

Specific Gravity/Relative Density: 0.83 Odor: Characteristic of vinegar and alcohol

Odor Threshold: N/A

Color: Colorless

Flammability (solid/gas): N/A

Vapor Density: N/A

Upper/Lower flammability or explosive limits: N/A

Vapor Pressure: N/A Evaporation Rate: N/A

Partition Coefficient: n-octanol/water: N/A

Viscosity: N/A

Auto-ignition temperature: N/A Solubility: Miscible in water

Decomposition Temperature: N/A

10. Stability and Reactivity

Reactivity:

Chemical Stability: Stable

Conditions of Stability/Instability: Instable under exposure to sources of ignition, heat or open flame.

Stabilizers needed: None

Safety issue indicated by appearance change: N/A

Other: N/A

Hazardous Reactions: N/A

Hazardous Polymerization: Does not occur

Conditions to avoid: Instable under exposure to sources of ignition, heat or open flame.

Classes of Incompatible Materials: Oxidizers, strong acids, strong bases, potassium dioxide, bromine pentafluoride, acetyl

bromide, acetyl chloride, platinum, sodium

Hazardous Decomposition Products: Thermal-oxidation degradation can produce oxides of carbon. Toxic gases and vapors (I.e. Carbon monoxide) may be released in a fire.

11. Toxicological Information

Likely Routes of Exposure

Eyes: Irritation. Skin: Irritation.

Inhalation: Dizziness, headache, nausea, narcosis





Emergency 1-800-424-9300 Contact (intl.) 1-352-323-3500

Endure™ Alcoholic Clarifier

Ingestion: May cause blindness, nausea, damage to gastrointestinal tract, liver, kidneys and cardiovascular system. Carcinogenic if ingested repeatedly over time (IARC List 1-Ethanol in alcoholic beverages)

Signs or Symptoms of Exposure: Irritation eyes, skin, nose; headache, drowsiness, lassitude (weakness, exhaustion), narcosis; cough; liver damage; anemia; reproductive, teratogenic effects

Effects from short term exposure (delayed, immediate, chronic): Irritation to the eyes, nose, throat; headache, dizziness, nausea, May cause blindness with repeat ingestion, damage to gastrointestinal tract, liver, kidneys and cardiovascular system

Acute Toxicity (Numerical Measures): Glacial Acetic Acid: LD50 (mammal, skin)=1060mg/kg; LD50 (rabbit, skin)=1060 mg/kg; LC50(inhalation, mouse)=5620 ppm/1H; LC50(inhalation, mouse)=5620 mg/m3/1H Ethyl Alcohol: LD50(oral,mouse)=3450 mg/kg; LC50(inhalation,mouse)=39000 mg/m3/4H

Carcinogenicity (NTP, IARC, OSHA): Not listed as a carcinogen.* *Note: Ethanol in alcoholic beverages is listed as IARC List 1 Carcinogenic to humans.

12. Ecological Information

Ecotoxicity: Acute Aquatic Effects Data for 100% Glacial Acetic Acid 96 h LC-50 (fathead minnow): > 100mg/L 48 h LC-50 (golden orfe): 410 mg/L 48 h LC-50 (mosquito fish): 251 mg/L 96 h LC-50 (daphnid): > 100 mg/L

Persistence and degradability: N/A

Bioaccumulation Potential (octanol-water partition coefficient, BCF): Oxygen Demand Data for 100% Glacial Acetic

Acid BOD-5: 340-880 mg/g BOD-20: 900 mg/g COD: 1,030 mg/g

Mobility in the soil: N/A

Adverse Environmental Effects: May cause adverse environmental effects.

13. Disposal Considerations

Recommended Disposal Containers: Check with your local waste authorities*

Recommended Disposal Methods: Do not dispose of in drains, check with your local waste authorities.*

Physical/Chemical Properties affecting Disposal: See section 2 and section 9 applicable information.*

Special Precautions for Landfill and Incineration Activities: Check with your local waste authorities.*

Waste Stream: Consult your local or regional authorities.*

14. Transport Information

UN Number: UN1170

UN Proper Shipping Name: Ethanol Solution

Transport Hazard Class(es): 3
Packing Group Number: □

Environmental Hazards (IMDG code):

Marine Pollutant: No

Transport in Bulk (IBC Code): N/A
Special Transport Precautions: N/A

15. Regulatory Information

OSHA: DOT: EPA: CPSC:



Emergency 1-800-424-9300 Contact (intl.) 1-352-323-3500

Endure™ Alcoholic Clarifier


16. Other Information

Revision Date: 2019-01-11

NFPA

Health	2
Fire Hazard	3
Reactivity	0
Specific Hazard	

National Fire Protection Association (USA) NFPA



Specific Hazard

HMIS

Health	2
Flammability	3
Physical Hazard	0
Personal Protection	

Hazardous Material Information System HMIS



Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.