



The **ESPO Path Slide Printer** is a wireless ready printer (OT Printer). Despite its minimal size, it has two independent magazines for slides so that it can automatically print on two types of glass. A front loading feeder is also available to print on a different slide that can already be covered with tissue, without changing the magazines. This allows positive immune controls to be labeled directly on the slide.

"Risk management" and "workability" are compatible

- Front loading for single slides
- Ultra-compact size
- Touch panel display
- WiFi, LAN, USB connection
- Excellent print quality



Technical Features

Part number	ESPO-1
Description	ESPO Slide Printer
Printing method	Line thermal transfer method
Print dot density	300 dpi
Printing speed	Continuous mode - about 20 slides / min
Print direction	0 °, 90 °, 180 °, 270 °
Print quality	Water · Alcohol · Xylene tolerant
Bar code types	UPC-E, CODE 39 · CODE 93 · CODE 128 · EAN 128 · NW-7 · QR code · micro QR code · DMC
Supply of slide glass	-way supply method (magazine x 2, front loading)
Slide glass removal	Stacker for exclusive order of each one (20 sheets)
Recommended Slides	Matsunami Fine Frost
Supported frost width	15 mm · 20 mm · 25 mm
Ink ribbon	Exclusive solvent resistance ink ribbon
Interface	Wired LAN · Wireless LAN (IEEE802.11b / g / n) · USB 2.0