Product Name: Pro-Par Clearant

Date: January 21, 2020

Page 1 of 6



SECTION 1: IDENTIFICATION

Product: Pro-Par Clearant

Product number: 510, 511, 515, 519

Synonyms: Xylene substitute

Recommended use: Laboratory chemical

Company

Anatech Ltd	24 hour Transportation Emergency	800.424.9300 CHEMTREC
1020 Harts Lake Road	Product Technical Information	800.262.8324, M-F, 8 AM-5 PM, ET
Battle Creek, MI 49037, USA	Supplier General Contact	800.262.8324, M-F, 8 AM-5 PM, ET

SECTION 2: HAZARD(S) IDENTIFICATION

Classification of substance

Flammable liquid (Category 3) Aspiration toxicant (Category 1)

Signal word

Danger

Hazard statement

Flammable liquid and vapor. May be fatal if swallowed and enters airway.

Pictogram





Precautionary statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating and lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/eye protection/face protection.

Response

If on skin/hair: Immediately remove all contaminated clothing. Rinse skin with water/shower.

If swallowed: Immediately call a poison center/doctor/physician.

Do NOT induce vomiting.

In case of fire: Use water fog, foam, dry chemical or carbon dioxide to extinguish.

Storage

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal

Dispose of contents/containers in accordance with governmental regulations.

Hazards not otherwise classified

None as defined under 29 CFR 1900.1200

Product Name: Pro-Par Clearant

Date: January 21, 2020

Page 2 of 6



SECTION 3: COMPOSITION AND INFORMATION ON INGREDIENTS

Chemical name	CAS#	Concentration
Paraffinic hydrocarbon	*	*
Propylene glycol ether	*	*

^{*} As per paragraph (i) of 29 CFR 1910.1200, formulation is considered a trade secret and specific chemical identity and exact percentage (concentration) have been withheld. Specific chemical identity and exact percentage composition will be provided to health professionals in accordance with applicable provisions of paragraph (i).

SECTION 4: FIRST-AID MEASURES

Description of first-aid measures

Inhalation	Remove victim to fresh air if coughing or difficulty in breathing is experienced. Consult a physician if symptoms persist or worsen. Administer oxygen or artificial respiration as needed.
Eye	Flush eyes for at least 15 minutes in an eyewash station. Consult a physician.
Skin	Remove contaminated clothing, including footwear; wash before reuse or discard. For minor exposure, wash affected area with water and mild soap, rinsing thoroughly. In cases of prolonged, repeated or extensive exposure, rinse affected area or entire body for at least 15 minutes. Consult a physician.
Ingestion	Call a poison control center immediately.

Important symptoms, acute and delayed

Mildly irritating to skin. Repeated exposure may cause skin dryness or cracking. Direct contact with eyes may cause temporary irritation.

Recommendations for immediate medical care and special treatment

If ingested, material may be aspirated into the lungs and cause pulmonary edema and pneumonitis. Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media

Use water fog, foam, dry chemical or carbon dioxide. Do not use straight streams of water.

Specific hazards arising from the product

Combustible. Vapors are heavier than air. Vapors may travel across the ground and reach remote ignition sources causing a flashback fire danger.

Special protective equipment/precautions for fire-fighters

Fire-fighters should use standard protective equipment and self-contained breathing apparatus. Use water spray to cool fire exposed surfaces.

Product Name: Pro-Par Clearant

Date: January 21, 2020

Page 3 of 6



SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions

Ensure adequate ventilation.

Avoid inhalation of vapors.

Avoid contact with skin and eyes.

Eliminate sources of ignition.

Take precautionary measures against static discharge.

Protective equipment

Wear protective gloves, impermeable aprons and splash-proof goggles.

Emergency procedures

Follow information listed in this section.

Methods and materials for containment and cleanup

Eliminate sources of ignition with large spills.

Take precautionary measures against static discharge.

Contain and soak up spill with inert absorbent material.

Discard absorbents and other contaminated solids in a suitable trash receptacle.

Dispose absorbents and other contaminated solids as a hazardous waste.

Wash contaminated area with soap and water.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes. Wear protective gloves, impermeable aprons and splash-proof goggles. With large volumes (55 gallon drum), material will accumulate static. Use proper grounding procedures for storage and when moving to transfer containers.

Conditions for safe storage including incompatibilities

Keep containers tightly closed. Store at room temperature. Consult local fire codes for additional storage information.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure limits

Chemical name	CAS#	Exposure Limit	Value
Paraffinic hydrocarbon	Trade secret	No regulatory limits allocated	_
Propylene glycol ether	Trade secret	OSHA (TWA)	100 ppm

Appropriate engineering controls

Good general room ventilation should be provided so that exposure limits are not exceeded. If required use explosion-proof ventilation to control vapors.

Personal protective measures

Respiratory protection	When risk assessment shows one is necessary, wear half-face filter respirator or a respirator with organic vapor cartridge.
Eye protection	Use splash-proof goggles. Do not use safety glasses. An eyewash station must be nearby, no more than 10 seconds away.
Skin protection Wear nitrile or chemical resistant gloves. Do not use latex surgical gloves for protection. Safety shower must be nearby, no more than 10 seconds away.	

Product Name: Pro-Par Clearant

Date: January 21, 2020

Page 4 of 6



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Property	Value
Appearance	Colorless, liquid
Odor	Characteristic
Odor threshold	No information available
рН	No information available
Melting point/freezing point	No information available
Initial boiling point and boiling range	155°C (311°F) (calculated), no other information available
Flash point	104°F (40°C) closed cup
Evaporation rate	No information available
Flammability (solid, gas)	No information available
Upper/lower flammability or explosive limits	No information available
Vapor pressure	No information available
Vapor density	5 (calculated)
Relative density	0.75 at 21°C
Solubility(ies)	Negligible
Partition coefficient: n-octanol/water	No information available
Auto-ignition temperature	No information available
Decomposition	No information available
Viscosity	No information available

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Non-reactive under normal conditions of use, storage and transport.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reaction

No information available.

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Temperatures greater than flash point.

Incompatible materials

Strong oxidizers

Hazardous decomposition products

Hazardous polymerization will not occur.

Product Name: Pro-Par Clearant

Date: January 21, 2020

Page 5 of 6



SECTION 11: TOXICOLOGICAL INFORMATION

Likely routes of exposure

Skin, eye

Symptoms related to physical, chemical and toxicological characteristics

Prolonged and/or repeated skin contact may cause temporary irritation.

Direct contact with eyes may cause temporary irritation.

Droplets of product aspirated into the lungs may cause pulmonary edema and pneumonitis.

Delayed and immediate effects

See information in sub-section above.

Chronic effects from short- and long-term exposure

No information available.

Numerical measures of toxicity

No data is known for the paraffinic hydrocarbon.

The following data are for 100% propylene glycol ether. Pro-Par Clearant has less than 15% propylene glycol ether.

	Acute toxicity, inhalation (rat)	7 hours LC ₅₀ >275 ppm
	Acute toxicity, dermal (rat)	LD ₅₀ >9500 mg/kg
Acute toxicity, oral (rat)		LD ₅₀ >5000 mg/kg

Assessment of other acute effects

May be fatal if swallowed and enters airway. Based on physio-chemical properties of the paraffinic hydrocarbon.

Carcinogenicity

None as defined by 29 CFR 1900.1200.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

This product is not classified as an environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect in the environment.

Persistence and degradability

No information available.

Bioaccumulative potential

No information available.

Mobility in soil

No information available.

Other adverse effects

No adverse environmental effects are expected.

SECTION 13: DISPOSAL CONSIDERATIONS

Product is suitable for distillation. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

Product Name: Pro-Par Clearant

Date: January 21, 2020

Page 6 of 6



SECTION 14: TRANSPORT INFORMATION

DOT (USA)

Not regulated as a dangerous good.

IATA

Proper Shipping Name: Petroleum products, n.o.s. (naptha solvent)

Identification Number: UN1268

Hazard Class: 3 Packing Group: III

Environmental hazard

Marine pollutant: No

SECTION 15: REGULATORY INFORMATION

OSHA Hazard Communication Standard

This product is considered hazardous in accordance with 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA (National Fire Protection Association) Rating

General note: The ratings provide information to emergency personnel on the fire hazards associated with the chemical. It is not descriptive of hazards under normal conditions of occupational use.

Health	1	Materials that, under emergency conditions, can cause significant irritation.
Flammability	2	Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Under normal conditions, these materials would not form hazardous atmospheres with air, but under high ambient temperatures or under moderate heating they could release vapor in sufficient quantities to produce hazardous atmospheres with air.
Instability	0	Materials that in themselves are normally stable, even under fire conditions.

Disclaimer

Anatech Ltd. believes the information in the SDS was obtained from reliable sources. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn may be from sources other than direct test data on the substance itself. It is the user's responsibility to determine suitability of the product for his/her own use, and to assure proper use and disposal of it to protect the safety and health of employees and the protection of the environment.

Date of preparation

January 21, 2020